U72 Option Switch Settings (Pulse/MDB/RS232 104U)

Supported bill USD 1, 5, 10, 20, 50, 100 6 Bills.

_		or to a one		<u> </u>	_, -	, 10	, – - ,	,			1110.			
	FUNCTI	ON	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
	Reject US	SD 1	ON											
*	Accept US	SD 1	OFF											
	Reject US	SD 5		ON										
*	Accept US	SD 5		OFF										
	Reject US	D 10			ON									
*	Accept US	D 10			OFF									
	Reject US	D 20				ON								
*	Accept US	D 20				OFF								
	Reject US	D 50					ON							
*	Accept US	D 50					OFF							
	Reject USI	D 100						ON						
*	Accept US	D 100						OFF						
	Harness Di	sable							ON					
*	Harness Ei	nable							OFF					
*	Inhibit Active HIGH									ON				
	Inhibit Active	e LOW								OFF				
	Power On S	tacker									ON			
*	Power On I	Reject									OFF			
	Slow Output Pulse	Lo 50 ms										ON		
	510w Output I tilse	Hi 300 ms										OIV		
	Fast Output Pulse	Lo 50 ms										OFF		
*	Tast Output Tursc	Hi 100 ms										OII		
	Reserved												ON	
*	Reserve	ed											OFF	
	Reserve	ed												ON
*	Reserve	ed												OFF

★Manufacture setting

Note: Please reset the bill acceptor after any changes on Dip switch.

U72 USD6(Pulse/MDB/RS232 104U)

DIP SWITCHES SETTING : 2(Pulse)

	FUNCTION	SW1	SW2	SW3	SW4
\bigstar	Reserved	ON			
	Reserved	OFF			
\bigstar	Pulse Mode		ON		
	Other Mode		OFF		
\bigstar	1 pulse / USD 1			OFF	OFF
	2 pulse / USD 1			OFF	ON
	4 pulse / USD 1			ON	OFF
	20 pulse / USD 1			ON	ON

[★]Manufacture setting

DIP SWITCHES SETTING: 2(MDB)

	FUNCTION	SW1	SW2	SW3	SW4
\bigstar	Reserved	ON			
	Reserved	OFF			
	Pulse Mode		ON		
\bigstar	Other Mode		OFF		
\bigstar	MDB			OFF	OFF
	RS232 104U			OFF	ON
	Reserved			ON	OFF
	Reserved		·	ON	ON

[★]Manufacture setting

Note:(1) Please reset the bill acceptor after any changes on Dip switch. (2)Please open the panel of front, and can see the DIP switch.

Currency Assign Data

Interface Bill value	Pulse	MDB	RS232 104U
BV1	USD 1	USD 1	USD 1
BV2	USD 5	USD 5	USD 5
BV3	USD 10	USD 10	USD 10
BV4	USD 20	USD 20	USD 20
BV5	USD 50	USD 50	USD 50
BV6	USD 100	USD 100	USD 100

DIP SWITCHES SETTING : 2(RS232 104U)

	FUNCTION	SW1	SW2	SW3	SW4
\star	Reserved	ON			
	Reserved	OFF			
	Pulse Mode		ON		
\bigstar	Other Mode		OFF		
	MDB			OFF	OFF
\star	RS232 104U			OFF	ON
	Reserved			ON	OFF
	Reserved			ON	ON

[★]Manufacture setting