



TP77P3B/P5 Protocol for RS232 104U / Pulse

ILS4 Support bill 20 、 50 、 100 、 200 (Israel)

DIP SW SETTING : 1

FUNCTION		SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10	
★	1 Pulse / ILS 10	OFF	OFF	OFF								
	2 Pulse / ILS 10	OFF	OFF	ON								
	3 Pulse / ILS 10	OFF	ON	OFF								
	4 Pulse / ILS 10	OFF	ON	ON								
	5 Pulse / ILS 10	ON	OFF	OFF								
	10 Pulse / ILS 10	ON	OFF	ON								
	20 Pulse / ILS 10	ON	ON	OFF								
	100 Pulse / ILS 10	ON	ON	ON								
	Fast Output Pulse	Lo=50ms Hi=100ms			ON							
★	Slow Output Pulse	Lo=50ms Hi=300ms			OFF							
	Inhibit level Active Low				ON							
★	Inhibit level Active High				OFF							
★	Accept ILS 20											ON
	Reject ILS 20					OFF						
★	Accept ILS 50											ON
	Reject ILS 50							OFF				
★	Accept ILS 100											ON
	Reject ILS 100								OFF			
★	Accept ILS 200											ON
	Reject ILS 200									OFF		
★	Reserved											
	Reserved										OFF	

★ Default setting

Note: Please reset the bill acceptor after any changes on Dip switch.

DIP SW SETTING : 2

FUNCTION		SW1	SW2	SW3	SW4
★	Pulse Normal High (NO)	ON			
	Pulse Normal Low (NC)	OFF			
★	Pulse Protocol		ON		
	RS232 Protocol		OFF		
	Straight			ON	
★	Turn Over			OFF	
	Reserved				ON
★	Reserved				OFF

★ Default setting

Note: Please reset the bill acceptor after any changes on Dip switch