



## **TP77P3B/P5 Protocol for RS232 104U / Pulse**

**SGD5 Support bill 2 、 5 、 10 、 50 、 100 (Singapore)**

### **DIP SW SETTING : 1**

FUNCTION		SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★	1 Pulse / SGD 1	OFF	OFF	OFF							
	2 Pulse / SGD 1	OFF	OFF	ON							
	3 Pulse / SGD 1	OFF	ON	OFF							
	4 Pulse / SGD 1	OFF	ON	ON							
	5 Pulse / SGD 1	ON	OFF	OFF							
	10 Pulse / SGD 1	ON	OFF	ON							
	20 Pulse / SGD 1	ON	ON	OFF							
	100 Pulse / SGD 1	ON	ON	ON							
	Fast Output Pulse	Lo=50ms Hi=100ms			ON						
★	Slow Output Pulse	Lo=50ms Hi=300ms			OFF						
	Inhibit level Active Low					ON					
★	Inhibit level Active High					OFF					
★	Accept SGD 2						ON				
	Reject SGD 2						OFF				
★	Accept SGD 5							ON			
	Reject SGD 5							OFF			
★	Accept SGD 10								ON		
	Reject SGD 10								OFF		
★	Accept SGD 50									ON	
	Reject SGD 50									OFF	
★	Accept SGD 100										ON
	Reject SGD 100										OFF

★ Default setting

Note: Please reset the bill acceptor after any changes on Dip switch.

### **DIP SW SETTING : 2**

FUNCTION		SW1	SW2	SW3	SW4
★	Pulse Normal High (NO)	ON			
	Pulse Normal Low (NC)	OFF			
★	Pulse Protocol		ON		
	RS232 Protocol		OFF		
	Straight			ON	
★	Turn Over			OFF	
	Reserved				ON
★	Reserved				OFF

★ Default setting

Note: Please reset the bill acceptor after any changes on Dip switch.